

02

N91-28216

NASA

Nuclear Thermal Propulsion

Space Transportation Propulsion
Technology Symposium

Gary L. Bennett

Program Manager
Propulsion, Power and Energy Division
Office of Aeronautics, Exploration and Technology
27 June 1990

DIRECT FISSION-THERMAL PROPULSION PROCESS

NUCLEAR ENERGY


FRAGMENT KINETIC ENERGY

THERMAL ENERGY


THERMODYNAMIC EXPANSION

DIRECTED THRUST

NUCLEAR ENGINE SCHEMATIC



Typical Rocket Propulsion Reactor




DIRECT FISSION-THERMAL PROPULSION -- ADVANTAGES

- HIGH SPECIFIC IMPULSE (860s - 1000s)
- HIGH THRUST-TO-WEIGHT
- NOT ENERGY LIMITED (AUX. POWER OPTIONS)
- REUSABLE
- THROTTLEABLE (25% - 100%)
- MONO-PROPELLANT
- MULTIPLE PROPELLANT CHOICES (H_2 , NH_3 , . . .)
- NEAR-TERM TECHNOLOGY (IT WORKS!)


MISSION APPLICATIONS OF DIRECT FISSION-THERMAL PROPULSION

- ORBIT TRANSFER VEHICLE
- LUNAR TUG
- PILOTED MARS MISSION
- EXTRA-TERRESTRIAL
RESOURCE UTILIZATION




MARS EXPEDITION CASE - IMLEO SENSITIVITY TO LAUNCH OPPORTUNITY


PROPULSION PERFORMANCE COMPARISON SCR AND GCR PILOTED MARS MISSIONS, QUICK TRIPS




PROPULSION PERFORMANCE COMPARISON NEP, SEP, AND SCR PILOTED MARS MISSION




Various Opportunities For Given MTV Propulsion Options



NTR MARS PERFORMANCE THRUST/WEIGHT AND ISP VARIATIONS




EXTRA-TERRESTRIAL PROPELLANT LANDER/HOPPER/ASCENT VEHICLE (DIRECT FISSION-THERMAL PROPULSION)




DIRECT FISSION-THERMAL PROPULSION SYSTEMS

	<u>NERVA</u>	<u>ANRE (INEL)</u>	<u>PBR (BNL)</u>
THRUST [kN]	333	65	44
I_{sp} [s]	825	900	900-1000
MASS FLOW [Kg/s]	41.2	7.4	4.5
POWER [MW _T]	1500	370	200
WEIGHT [10^3 Kg]	10.4	2.1	0.6
THRUST/WEIGHT	32	31	73
FUEL	UC	UC-ZrC-C	UC-ZrC
MODERATOR	C	ZrH	LiH, Be, ZrH

Nuclear Rocket Program




NERVA Engine Technology Testing Test Stand Superstructure



**What we are attempting to make
is a flyable compact reactor,
not much bigger than an office
desk, that will produce the
power of Hoover Dam from a
cold start in a matter of minutes**

**-- Dr. Glenn T. Seaborg
Chairman
Atomic Energy Commission**

Evolution of Rover Reactors



NERVA/Rover Reactor System Test Sequence


		'59	'60	'61	'62	'63	'64	'65	'66	'67	'68	'69	'70	'71	'72
NERVA Program	NRX Reactor Test				NRX-A1				NRX-A3		NRX-A6				
	Engine Tests				NRX-A2				NRX-A5						
Rover Program	KIWI		KIWI A		KIWI B1 B			KIWI B4 D							
			KIWI A		KIWI B4 A			KIWI TNT							
					KIWI B1 A			KIWI B4 E							
	Phoebus						Phoebus 1A				Phoebus 1B				
											Phoebus 2A				
	Pewee										Pewee				
	Nuclear Furnace													NF-1	

Flexibility Demonstrated in Ground Experimental Engine (XE) Test

TEST PERIOD, 3/20/69-8/28/69


EXPERIMENTS CONDUCTED

STARTUP INVESTIGATIONS	15
PERFORMANCE CHARACTERISTICS AT HIGH POWER	6
ENGINE DYNAMIC PERFORMANCE	10
FACILITY EVALUATION	4



SUMMARY - 28 STARTUPS
3 HOURS 48 MINUTES OF OPERATION

Operating Time vs Temperature for Nuclear Rocket Program



Major System Test Results

- Demonstrated power capability
 - 1100 MWt in NRX (55,000 lbs thrust)
 - 4400 MWt in Phoebus (220,000 lbs thrust)
- Demonstrated power, temperature and flow stability
 - High specific impulse (800-900 seconds)
 - High thrust startup
- Demonstrated reactor/engine endurance – 60 minutes in NRX-A6
- Demonstrated reactor/engine maneuverability - 28 startup cycles in NRX-XE
- Demonstrated reactor fuel – 10 hours 40 minutes and 64 cycles

NERVA TECHNOLOGY HAS SYNERGISTIC APPLICATIONS

Steady-State Power




- 10's of MWe for electric propulsion

Direct thermal propulsion


- 15,000 to 250,000 pounds of thrust

Dual Power Systems

- High direct thrust (e.g., 75,000 pounds) plus low electric propulsion (e.g., 1 MWe)




Versatility




NERVA DESIGN - STATUS


- DEVELOPED DURING PROJECT ROVER
- FULL POWER, FULL DURATION TESTED
- FLIGHT QUALIFIABLE DESIGN UNDER WAY AT CONCLUSION OF PROJECT ROVER
- EXPERTISE STILL AROUND (JUST BARELY)
- WESTINGHOUSE FULL-DESIGN BLUEPRINTS INTACT
- LANL CAN STILL EXTRUDE FUEL SEGMENTS
- FUEL SEGMENT TEST FACILITIES AVAILABLE
- FULL SCALE TEST FACILITIES UNAVAILABLE

SMALL/ADVANCED NUCLEAR ROCKET ENGINE (SNRE/ANRE - LANL/INEL)



PARTICLE BED REACTOR DESIGN






NASA

NUCLEAR PROPULSION THRUST PLAN

OAET

~~PROPULSION, POWER & ENERGY~~

5.3 TECHNOLOGY DEVELOPMENT STRATEGY



EXECUTIVE SUMMARY**KEY TECHNICAL ISSUES**

Safety/safeguards/QA
(during all program phases)
Qualification/acceptance test strat.
Reliability and fault tolerance
High Performance engines
(including reactors)
Reusability/restart capability
Reactor Fuel
Structural Aspects
Turbomachinery
Vessels/Nozzles
Pumps/Valves
Diagnostic Capability
Control Systems (neutronics/
I&C)

Power Processing Units
(NEP)
Thrusters (NEP)
Space operations
- radiation shielding
- design criteria for in-space
operation and
maintenance
Propellants/Prop. handling
Thermal hydraulics
Thermal Management
Materials
Lifetime
Mass/Volume Limitations
In-situ Prop. Utilization

LET'S GO TO MARS!

PRESENTATION 1.4.3

FUSION PROPULSION

